HEUEIVED CENTRALFAX CENTER

OCT 1 0 2007

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (previously presented): A synchronous network, comprising:

nodes transmitting data to one another in a predefined sequence for a predefined duration, a plurality of said nodes outputting a synchronization signal defining a reference time for a synchronization of said nodes, said synchronization signal having a duration which is longer than a maximum signal transit time occurring inside the network;

a respective node of said nodes wishing to synchronize with one or more others of said nodes outputting the synchronization signal and further data which identifies said respective node in a time slot assigned to said respective node after outputting the synchronization signal or receiving the synchronization signal or said nodes; and

said synchronization signal having at least one of a time profile and a duration that the synchronization signal can be identified as the synchronization signal even if other

Page 2 of 11

synchronization signals which are output by different ones of said nodes are overlapping on one another.

Claim 2 (canceled)

Claim 3 (original): The network according to claim 1, wherein the synchronization signal is encoded using one of an NRZ code, a XERXES code, and a Manchester code.

Claim 4 (canceled).

Claim 5 (currently amended): A synchronous network, comprising:

nodes transmitting data to one another in a predefined sequence for a predefined duration, a plurality of said nodes outputting a synchronization signal defining a reference time for a synchronization of said nodes, said synchronization signal having a duration which is longer than a maximum signal transit time occurring inside the network, wherein a respective node of said nodes wishing to synchronize with one or more others of said nodes initially observes for a predetermined time to determine whether another one of said nodes is outputting the synchronization signal or other data, and, if another one of said nodes is not outputting the

synchronization signal or other data, said respective node outputs the synchronization signal; and

said respective node wishing to synchronize with one or more others of said nodes outputting further data which identifies said respective node in a time slot assigned to said respective node after outputting the synchronization signal or receiving the synchronization signal from another one of said nodes; and

of said nodes defining a chronological position of time slots assigned to it as a function of the synchronization signal which is output by said respective node or received by said respective node from another one of said nodes.

Claims 6 - 8 (canceled)

Claim 9 (original): The network according to claim 1, wherein the synchronization signal is output in a specific time slot of a time slot cycle used.

Claim 10 (original): The network according to claim 9, wherein the specific time slot is a global time slot in which

all of said nodes are allowed to output specific signals and specific data.

Claim 11 (original): The network according to claim 1, wherein all of said nodes output the synchronization signal.

Claim 12 (currently amended): The network according to claim

5, wherein A synchronous network, comprising:

nodes transmitting data to one another in a predefined
sequence for a predefined duration, a plurality of said nodes
outputting a synchronization signal defining a reference time
for a synchronization of said nodes, said synchronization
signal having a duration which is longer than a maximum signal
transit time occurring inside the network, wherein a
respective node of said nodes wishing to synchronize with one
or more others of said nodes initially observes for a
predetermined time to determine whether another one of said
nodes is outputting the synchronization signal or other data,
and, if another one of said nodes is not outputting the
synchronization signal or other data, said respective node
outputs the synchronization signal;

said respective node wishing to synchronize with one or more others of said nodes outputting further data which identifies

said respective node in a time slot assigned to said

respective node after outputting the synchronization signal or

receiving the synchronization signal from another one of said

nodes; and

said respective node wishing to synchronize with one or more others of said nodes defines defining a chronological position of time slots assigned to it as a function of the synchronization signal which is output by said respective node or received by said respective node from another one of said nodes and as a function of received data which others of said nodes have output in their assigned time slots, in order to identify itself to others of said nodes.

Claim 13 (currently amended): The network according to claim

5, wherein A synchronous network, comprising:

nodes transmitting data to one another in a predefined

sequence for a predefined duration, a plurality of said nodes

outputting a synchronization signal defining a reference time

for a synchronization of said nodes, said synchronization

signal having a duration which is longer than a maximum signal

transit time occurring inside the network, wherein a

respective node of said nodes wishing to synchronize with one

or more others of said nodes initially observes for a

nodes is outputting the synchronization signal or other data, and, if another one of said nodes is not outputting the synchronization signal or other data, synchronization signal or other data, said respective node outputs the synchronization signal;

said respective node wishing to synchronize with one or more others of said nodes outputting further data which identifies said respective node in a time slot assigned to said respective node after outputting the synchronization signal or receiving the synchronization signal from another one of said nodes; and

said respective node wishing to synchronize with one or more others of said nodes <u>defines</u> <u>defining</u> a chronological position of time slots assigned to it as a function of received data which others of said nodes have output in their assigned time slots, in order to identify itself to others of said nodes.

Claims 14 - 15 (canceled)